

one B1 ~~MEMORY CARD CONNECTOR~~

Background of Invention

1. Field of the Invention: This invention relates to a connector, and more particularly, to a memory card connector for use in notebook computers, PC printers and palmtop computers which can expand the space under the connector for installing electronic components and can be maintained easily.
2. Brief Description of the Prior Developments: Rapid progress in various personal computer technologies and improvements in shrinking-size components may make notebook computers the most popular computers in the computer market in the future. For note book computers (or PC printers, palmtop computers) equipped with PCMCIA (Personal Computer Memory Card International Association) slots, memory card connectors are used for connecting PCMCIA cards loaded in the slots to the mainboard of the notebook. A conventional memory card connector is usually installed on a mainboard by using SMT (Surface Mounting Technology) which solders the pins of the connector directly to the surface of the mainboard. Such rigid connection usually causes serious maintenance problems if the connector is to be replaced later on. Besides, the bottom of the conventional memory card connector is directly placed on the surface of the mainboard. The occupied area under the connector can not be used for other purposes such as installing electronic components. Such waste in mainboard space is usually not tolerable in notebook computers which have very restrictive mainboard space.

Summary of the Invention

The memory card connector of the present invention may be detachably mounting on a mainboard. The memory card connector comprises a header and a carrier connected to the header, wherein the header is provided with a plurality of pins extended in both inward and outward directions, and a vertical circuit board is electrically and securely connected to the outward pins of the header. The lower end of the circuit board is detachably inserted into a female connector of the mainboard.

In the memory card connector of the present invention the height of the circuit board of the connector can also be set according to the requirement of a specific application of the connector so that the space (stand-off) between the connector and the mainboard can be properly utilized.

Additionally, two memory card connectors which may be stacked together, such that the outward pins of the upper connector are longer than the outward pins of the lower connector and the two vertical circuit boards respectively connected to the upper and lower connectors are detachably and vertically connected to two corresponding female connectors of the mainboard separately.

Brief Description of the Drawings

The memory card connector of the present invention will be more fully understood and appreciated by reference to the written specification in conjunction with the accompanying drawings in which:

Fig. 1 is an exploded view of a memory card connector and its associated mainboard according to the present invention;

Fig. 2 is a side elevational view illustrating a memory card connector installed on a mainboard according to the present invention;

Fig. 3 is a side elevational view illustrating two memory card connectors stacked together and installed on a mainboard according to the present invention; and

Fig. 4 is a perspective view illustrating a conventional memory connector installed on a mainboard.

Detailed Description of the Preferred Embodiments

Referring now to Fig. 1, a memory card connector 1 according to the present invention comprises a header 10 and a carrier 12 connected to the header 10. The connection between the header 10 and the carrier 12 can be fixed or separated in the known manner, which is not the characteristic feature of the invention and is omitted in the description hereinafter. The header 10 is provided with a plurality of pins 101 extended in both inward and outward directions. The inward pins 101 extending from the inward edge 102 of the header are used for inserting a memory card (not shown) to be received in the carrier 12. A vertical circuit board 14 is electrically and securely connected to the outward pins 103 extending from the outward edge 104 of the header 10. A female connector 3 is securely mounted to the surface of a mainboard 2 for mounting the memory card connector 1. The lower end of the vertical circuit board 14 is detachably inserted into the female connector 3 to effect electrical connection.

With reference to Fig. 2, in installing the connector 1 to the mainboard 2, the lower end of the circuit board 14 is directly plugged to the female connector 3 and the bottom of connector 1 is horizontally supported by four studs 21 provided on the mainboard 2. The connector 1 can be fastened to the studs 21 by using screws (not shown) respectively received in the four studs 21 passing through four screw mounting holes 120 of connector 1. The height of the circuit board 14 is set according to the requirement of a specific

application of the memory card connector so that the space between the memory card connector 1 and the mainboard 2 can be properly utilized.

In Fig. 3, two memory card connectors 1 and 1' are stacked together and installed on the mainboard 2. The outward pins 103' of the upper connector 1' are longer than the outward pins 103 of the lower connector 1. Circuit board 14' in the upper connector 1' is larger to fit the real height as required. Two vertical circuit boards 14' and 14 respectively connected to the upper and lower connectors 1' and 1 are detachably and vertically connected to two corresponding female connectors 3' and 3 of the mainboard 2 separately.

In Fig. 4, a conventional memory connector 4 installed on a mainboard 5 is illustrated. The connector 4 comprises a plurality of bending pins 41 which are directly soldered to the mainboard 5 by using SMT. As compared with the connector 1 in accordance with the present invention, it is difficult to replace the known installed connector 4 because it is securely fixed on the mainboard 5 which will cause a serious problem in maintenance. Furthermore, there is no space available under connector 4 for use such as installing electronic components.

It will be appreciated that a memory card connector has been described which provides an efficient and economical means for providing space for electronic components.

It will also be appreciated that a method for advantageously connecting a memory card connector to a main circuit board has been provided in which the outwardly extending pins are connected to a vertical circuit board and that vertical circuit board is connected to the main circuit board.

